

Amendment  
Serial No. 10/654,892  
Attorney Docket No. 053432

**AMENDMENTS TO THE CLAIMS**

The following listing of claims replaces all prior versions of claims in the application.

1. (Currently Amended) A vehicle inner belt molding to be fitted along an interior of an opening edge of an elevating window in a vehicle, wherein the vehicle has a door inner panel and a trim board being attached to the door inner panel and having a downward flange portion protruding downwardly from a position that is interior of an outer end of the trim board and that is exterior of an upper-edge flange portion of the door inner panel, the vehicle inner belt molding comprising:

a fitting portion to be attached to the door inner panel; and

a sealing lip formed integrally with an exterior side of the fitting portion to be in elastic contact with an inner surface of the elevating window,

wherein the fitting portion has an upward opening groove fittable with the downward flange portion,

wherein the upward opening groove has a projection projecting from a wall of the upward opening groove, the projection extending longitudinally along the entire length of the vehicle inner belt molding, and

wherein the fitting portion includes an outer fitting portion having the upward opening groove and an inner fitting portion having a downward opening groove for receiving the upper-edge flange portion of the door inner panel.

2. (Canceled).

Amendment  
Serial No. 10/654,892  
Attorney Docket No. 053432

3. (Previously Presented) The vehicle inner belt molding according to claim 1, wherein the projection is a gripping lip provided on a side wall of the upward opening groove and configured to grip the downward flange portion.

4. (Previously Presented) The vehicle inner belt molding according to claim 1, wherein:

the projection is a gripping lip provided on a side wall of the upward opening groove and configured to grip the downward flange portion; and

the downward opening groove is provided with at least one gripping lip configured to grip the upper-edge flange portion.

5. (Previously Presented) The vehicle inner belt molding according to claim 1, further comprising:

a cloth pressing piece protruding upward from the exterior side of the fitting portion;

wherein the cloth pressing piece is configured to press an end portion of a cloth covering a surface of the trim board when the downward flange portion is fitted into the upward opening groove.

6. (Currently Amended) The vehicle inner belt molding according to claim 1, wherein:

the fitting portion has ~~one or more~~ positioning ~~slits~~ partially crossing therethrough; and

Amendment  
Serial No. 10/654,892  
Attorney Docket No. 053432

the one or more positioning ~~slit~~ is slits are configured to be engageable with ~~[[a]]~~ one or more positioning ~~[[rib]]~~ ribs projecting downward from a back surface of the trim board.

7. (Currently Amended) The vehicle inner belt molding according to claim 6, wherein a thickness of the one or more positioning ~~[[rib]]~~ ribs is smaller than a width of the one or more positioning ~~[[slit]]~~ slits.

8. (Currently Amended) The vehicle inner belt molding according to claim 7, wherein:

at least two of said positioning slits are arranged at a predetermined interval in a longitudinal direction of the fitting portion and are configured to receive at least two of said positioning ribs; and

the ~~[[two]]~~ positioning slits are formed so that the opposing surfaces of the ~~[[two]]~~ positioning ribs are brought into contact with inner-side surfaces of the ~~[[two]]~~ positioning slits when the ~~[[two]]~~ positioning ribs are fitted into the ~~[[two]]~~ positioning slits.

9. (Currently Amended) The vehicle inner belt molding according to claim 7, wherein:

at least two of said positioning slits are arranged at a predetermined interval in a longitudinal direction of the fitting portion and are configured to receive at least two of said positioning ribs; and

Amendment  
Serial No. 10/654,892  
Attorney Docket No. 053432

the [[two]] positioning slits are formed so that the outer-side surfaces of the [[two]] positioning ribs are brought into contact with outer-side surfaces of [[two]] adjacent positioning slits when the [[two]] positioning ribs are fitted into the [[two]] positioning slits.

10. (Previously Presented) The vehicle inner belt molding according to claim 6, further comprising:

a core member embedded in the fitting portion in the longitudinal direction thereof, the core member made of a material having an expansion resistance and a rigidity both larger than those of the fitting portion;

wherein the core member has a cross sectional shape substantially similar to that of at least a part of the fitting portion.

11. (Original) The vehicle inner belt molding according to claim 1, wherein the fitting portion is made of thermoplastic elastomer material.

12. (Original) The vehicle inner belt molding according to claim 1, wherein the sealing lip is made of a material which is capable of fusion-bonding to the fitting portion and which is softer and more elastic than the fitting portion.

Amendment  
Serial No. 10/654,892  
Attorney Docket No. 053432

13. (Currently Amended) A sealing structure of an elevating window in a vehicle, comprising:

a vehicle inner belt molding to be fitted along an interior side of an opening edge of the elevating window, the vehicle inner belt molding including a fitting portion configured to be attached to the vehicle and a sealing lip formed integrally with an exterior side of the fitting portion to be in elastic contact with an inner surface of the elevating window; and

a trim board disposed inside of the elevating window, the trim board having a downward flange portion protruding therefrom;

wherein the fitting portion has an upward opening groove fittable with the downward flange portion and,

wherein the vehicle inner belt molding is attached to the trim board by inserting the downward flange portion into the upward opening groove, and

wherein the upward opening groove has a projection projecting from a wall of the upward opening groove, the projection extending longitudinally along the entire length of the vehicle inner belt molding.

14. (Currently Amended) The sealing structure according to claim 13,

wherein the fitting portion includes an outer fitting portion having the upward opening groove and an inner fitting portion to be positioned interior of the outer fitting portion;

the outer fitting portion has one or more positioning slits partially crossing therethrough;

the trim board has ~~[[a]]~~ one or more positioning ~~[[rib]]~~ ribs projecting downward from a back surface thereof; and

the inner belt molding is attached to the downward flange portion while being positioned in a longitudinal direction by inserting the one or more positioning ~~[[rib]]~~ ribs into the one or more positioning slits.

15. (Currently Amended) The sealing structure according to claim 13, wherein the projection is a gripping lip provided on ~~a-side~~ side wall of the upward opening groove and configured to grip the downward flange portion.

16. (Previously Presented) The sealing structure according to claim 13, wherein the projection is a holding lip provided on a bottom wall of the upward opening groove, said holding lip being elastically deformable.

17. (Currently Amended) The sealing structure according to claim 13, wherein the projection is a latching stripe provided on ~~a-side~~ side wall of the upward opening groove, said latching stripe being configured to be received within a recess on the downward flange portion.

18. (Currently Amended) A sealing structure of an elevating window in a vehicle, comprising:

a vehicle inner belt molding to be fitted along an interior side of an opening edge of the elevating window, the vehicle inner belt molding including a fitting portion configured to

Amendment  
Serial No. 10/654,892  
Attorney Docket No. 053432

be attached to the vehicle and a sealing lip formed integrally with an exterior side of the fitting portion to be in elastic contact with an inner surface of the elevating window; and

a trim board disposed inside of the elevating window, the trim board having a downward flange portion protruding therefrom,

wherein the fitting portion has an upward opening groove fittable with the downward flange portion,

wherein the vehicle inner belt molding is attached to the trim board by inserting the downward flange portion into the upward opening groove,

wherein the fitting portion has ~~one or more~~ positioning ~~slits~~ slits partially crossing therethrough, and

wherein a back surface of the trim board has ~~one or more~~ positioning ~~ribs~~ ribs projecting downward therefrom, the ~~one or more~~ positioning ~~ribs~~ being engageable with the ~~one or more~~ positioning ~~slits~~ slits, and the ~~one or more~~ positioning ~~ribs~~ ribs being unitary with the trim board, and

wherein the upward opening groove has a projections projecting from a wall of the upward opening groove, the projection extending longitudinally along the entire length of the vehicle inner belt molding.

19. (Previously Presented) The vehicle inner belt molding according to claim 1, wherein the projection is a holding lip provided on a bottom wall of the upward opening groove, said holding lip being elastically deformable.

Amendment  
Serial No. 10/654,892  
Attorney Docket No. 053432

20. (Currently Amended) The vehicle inner belt molding according to claim 1, wherein the projection is a latching stripe provided on ~~a side~~ said wall of the upward opening groove, said latching stripe being configured to be received within a recess on the downward flange portion.